

# Fog Maker Lince



Pressure 60bar  
Fan jet 7m  
13/30 nozzles

**NEW**



Lince Fog maker  
ideal for  
suppression  
of fine dust



Indoor disinfection  
with Lince  
Disinfettante fog  
maker



Lince 1




Lince 4

## Fog maker Lince

Mobile high pressure fog maker complete with fan and ring of nozzles, 60bar 1/4 l/min pump module, 30L tank (Lince 1), ON-OFF electric panel. Fan jet: 7m.

- Ideal for sanitization, odour and pollution (PM2.5 and PM10) suppression of small to medium areas
- Practical and handy, with 30 minutes autonomy (Lince 1)

### Technical features



## Technical features

### Axial pump with 2 pistons



Code	Model	Pressure	Flow rate	N. nozzles	Drop size	Power (3x400V-50Hz)	Peso	Preventive maintenance 500 hrs (standard)	Preventive maintenance 1000 hrs (optional)	Page
<b>ZX.8201</b>	<b>LINCE 1</b>	60bar	1l/min	13	12mcr	0,75Kw	60kg	ZX.50IBG19	ZX.100IBG19	112

### Axial pump with 3 pistons **NEW**



Code	Model	Pressure	Flow rate	N. nozzles	Drop size	Power (3x400V-50Hz)	Peso	Preventive maintenance 500 hrs (standard)	Preventive maintenance 1000 hrs (optional)	Page
<b>ZX.8204</b>	<b>LINCE 4</b>	60bar	4l/min	30	12mcr	1,5Kw	70kg	ZX.50IBG20	ZX.100IBG20	112



Accessories  
page 446



## Technical features

- **Frame** in painted steel sheet
- **Air flow rate:** 3510 m<sup>3</sup>/h
- **Coverage:** 10 m<sup>2</sup>
- **Power absorption:** 0.55Kw 2800g/min
- **Fan jet:** 7m 21°C (without wind)
- **Elevation:** 0° +30° manual
- **Fan diameter:** 410mm
- **Noise:** < 80Lw
- **Protection rating:** IP54
- **Dimensions WxLxH:** 800x650x1200mm

## Lince 1

- **No. of nozzles :** 1 ring AISI 304 stainless steel with 13 nozzles
- **Professional motorpump** 1450g/min, 200W, axial movement, 2 ceramic pistons
- **Tank** 30L for 1l/min version

## Lince 4

- **No. of nozzles :** 1 ring AISI 304 stainless steel with 30 nozzles
- **Professional motorpump** 1450g/min, 950W, axial movement, 3 ceramic pistons in ceramic steel
- **Solenoid valve** inlet water 230V
- **5" water inlet kit** with pressure stabilizer